

暖气/热水管 RH150



- 温度范围：-40°C (-40°F) 到+120°C (+248°F)
- 内 层：黑色、光滑、耐热橡胶化合物
- 加 强 层：高强度合成芯
- 外 层：黑色、光滑橡胶化合物，耐热、耐侵蚀、耐磨损
- 管 长：40 (132英尺)，提供软管接头或加工扣压
- 印 记：绿色条纹

应用热水交换输送，水循环；制冷设备；热空气，汽车制造；发动机冷却管；心轴橡胶热水管；适用于工业净化工设备；水冷装置系统。

| 内径 | 产品型号 | 内径/外径 mm |
|--------|------------|-------------|
| 1/2 | RH150-0050 | 13×23 |
| 5/8 | RH150-0063 | 16×26 |
| 3/4 | RH150-0075 | 19×30 |
| 7/8 | RH150-0088 | 22×33 |
| 1 | RH150-0100 | 25×36 |
| 1-1/8 | RH150-0113 | 28×39 |
| 1-3/16 | RH150-0119 | 30×41 |
| 1-1/4 | RH150-0125 | 32×43 |
| 1-3/8 | RH150-0138 | 35×46 |
| 1-1/2 | RH150-0150 | 38×49 |
| 1-9/16 | RH150-0156 | 40×51 |
| 1-5/8 | RH150-0163 | 42×53 |
| 1-3/4 | RH150-0175 | 45×56 |

| 内径 | 产品型号 | 内径/外径 mm |
|--------|------------|-------------|
| 1-7/8 | RH150-0188 | 48×60 |
| 2 | RH150-0200 | 51×64 |
| 2-1/8 | RH150-0213 | 55×68 |
| 2-1/4 | RH150-0225 | 57×70 |
| 2-3/8 | RH150-0238 | 60×73 |
| 2-1/2 | RH150-0250 | 63×77 |
| 2-9/16 | RH150-0256 | 65×78 |
| 2-5/8 | RH150-0263 | 68×81 |
| 2-3/4 | RH150-0275 | 70×84 |
| 2-7/8 | RH150-0288 | 73×87 |
| 3 | RH150-0300 | 76×89 |
| 3-1/8 | RH150-0313 | 80×94 |
| 3-1/4 | RH150-0325 | 82×96 |

| 内径 | 产品型号 | 内径/外径 mm |
|-------|------------|-------------|
| 3-3/8 | RH150-0338 | 85×99 |
| 3-1/2 | RH150-0350 | 90×104 |
| 3-3/4 | RH150-0375 | 95×109 |
| 4 | RH150-0400 | 102×116 |
| 4-1/2 | RH150-0450 | 114×128 |
| 5 | RH150-0500 | 127×141 |
| 5-1/2 | RH150-0550 | 140×154 |
| 6 | RH150-0600 | 152×166 |
| 6-5/8 | RH150-0663 | 168×182 |
| 7 | RH150-0700 | 178×194 |
| 8 | RH150-0800 | 203×220 |
| 8-5/8 | RH150-0863 | 220×235 |